Proposals for IRAM Telescopes

The deadline for submission of observing proposals on IRAM telescopes, both the interferometer and the 30m, is

15 March 2007, 17:00 CET (UT + 1 hours)

The scheduling period extends now from June 1 to November 30. Proposals should be submitted through our web–based submission facility. Instructions are found on our web page at URL:

http://www.iram.fr/GENERAL/submission/submission.html

The submission facility will be opened about three weeks before the proposal deadline. Proposal form pages and the 30m time estimator are available now.

Please avoid last minute submissions when the network could be congested. As an insurance against network congestion or failure, we still accept, in well justified cases, proposals submitted by:

- fax to number: (+33) 476 42 54 69 or by
- ordinary mail addressed to:
  IRAM Scientific Secretariat,
  300, rue de la piscine,
  F-38406 St. Martin d'Hères, France

Proposals sent by e–mail are not accepted. Color plots will be printed/copied in grey scale. If color is considered essential for the understanding of a specific figure, a respective remark should be added in the figure caption. The color version may then be consulted in the electronic proposal by the referees.

Soon after the deadline the IRAM Scientific Secretariat sends an acknowledgement of receipt to the Principal Investigator of each proposal correctly received, together with the proposal registration number. To avoid the allocation of several numbers for the same proposal, send in your proposal *only once*. Note that the web facility allows cancelation and modification of proposals before the deadline. The facility also allows to view the proposal in its final form as it appears after re–compilation at IRAM. We urge proposers to make use of this possibility as we always receive a number of corrupted proposals (figures missing, blank pages, etc.).

Valid proposals contain the official cover page, up to two pages of text describing the scientific aims, and up to two more pages of figures, tables, and references. Proposals should *not exceed these 5 pages* of scientific material. Except for the technical pages for the interferometer, longer proposals will be cut.

The cover page, in postscript or in LaTeX format, and the LaTeX style file `proposal.sty` may be obtained from the IRAM web pages[1] at URL `../GENERAL/submission/proposal.html`. In case of problems, contact the secretary, Cathy Berjaud (e–mail: `berjaud@iram.fr`). Please, make sure that your proposals use the current form pages.

In all cases, indicate on the proposal cover page whether your proposal is (or is not) a *resubmission* of a previously rejected proposal or a *continuation* of a previously accepted interferometer or 30m proposal. We request that the proposers describe very briefly in the introductory paragraph (automatically generated header "Proposal history: ") why the proposal is being resubmitted (e.g. improved scientific justification) or is proposed to be continued (e.g. last observations suffered from bad weather).

Do not use characters smaller than 11pt. This could render your proposal illegible when copied or faxed. If we notice any formal problems before the deadline, we will make an effort to contact the principal investigator and solve the problem together.

Applications for **zero spacing observations** have been simplified. If the need for complementary 30m observations is evident already at the time when the PdB interferometer proposal is prepared, just note this need on the interferometer proposal. A separate proposal for the 30m telescope is not required. The blank form for interferometer proposals contains a bullet, labelled "zero spacing" which should then be checked. The interferometer style file will prompt for an additional paragraph in which the scientific need for the zero spacings should be decribed. It is essential to give here all observational details, including size of map, sampling density and rms noise, spectral resolution, receiver configuration and time requested.

A mailing list has been set up for astronomers interested in being notified about the availability of a new Call for Proposals. A link to this mailing list is on the IRAM web page. The list presently contains all users of IRAM telescopes during the last 2 years. Please check that your email address in this list is correct, and point out the existence of this list to interested colleagues.

J.M. Winters & C. Thum

[1] from here on we give only relative URL addresses. In the absolute address the leading two dots (..) have to be replaced by the address of one of our mirror sites: http://www.iram.fr or http://www.iram.es.

Travel funds for European astronomers

IRAM is one of the organizations participating in the RadioNet project, an initiative funded by the European Commission within the FP6 Programme to improve and encourage communication among astronomers of the European Community and associated countries. Transnational access (TNA) is the largest RadioNet programme and provides funding for travel expenses incurred by eligible users for carrying out their observations or reducing their data. As a partner of RadioNet, IRAM has now some limited TNA funds to pay travel expenses for eligible users. Detailed information about user eligibility, TNA contacts, policies and travel claims for the IRAM 30m telescope and Plateau de Bure Interferometer can be found on the RadioNet home page at `http://www.radionet-eu.org`.

Observers requesting TNA support will be asked to provide the necessary personal and professional information to IRAM. Funding through RadioNet should be acknowledged in publications resulting from TNA supported observations.

R. Neri & C. Thum

Call for Observing Proposals on the 30m Telescope

Summary

Proposals for three types of receivers will be considered for the coming summer semester:

1. the observatory's set of four dual polarization heterodyne receivers centered at wavelengths of 3, 2, 1.3, and 1.1 mm.
2. the 9 pixel dual–polarization heterodyne receiver array, HERA, operating at 1.3 mm wavelength
3. a 1.2 mm bolometer array with 37 or 117 pixels

In total, about 2800 hours of observing time will be available, which should allow scheduling of a few longer programmes (up to ~ 150 hours).

The main news, proposal formalities, details of the various receivers, and observing modes are described below.

What is new?

Since November 2005, the telescope runs under a VME and Linux based new control system (NCS). While some optimization, mainly related to telescope tracking and timing, is still going on, virtually all functionality of the old control system has been recovered. Notable exceptions are the coordinate system (only J2000 is currently supported) and the `RASTER` command. OTF, ONOFF or TRACKING (with frequency switching) commands together with SIC loops should be used instead. Observations with the rotated wobbler (non–azimuth wobbling directions) which are of interest mainly for bolometer mapping, are possible again.

Remote observing will be available from our Granada office, and later during the summer semester also from Grenoble and, possibly, Bonn.

The NCS team maintains a detailed web page (../IRAMES/ncs30m) where the current status is in depth.

The **dual polarization HERA** is operational together with its backends for high (VESPA) and low spectral resolution (WILMA, 4 MHz filters). Although tuning parameters are now available for a large range of frequencies, it is still recommended to send us HERA frequencies in advance.

Like last semester, a **bolometer array**, preferentially the 117–channel MAMBO II, which should be used for observing time estimates, will be available. HERA and bolometer observations will be organized in observing pools.

Applications

On the official cover page, please fill in the line 'special requirements' **if you request either polarimetric observations or service observing**. If the observations need or have to avoid specific dates, enter them here. If there are periods when you cannot observe for personal reasons, please specify them here.

We insist upon receiving, with proposals for heterodyne receivers, a complete list of frequencies corrected for source redshift (to 0.1 GHz) and precise positions. If in very special cases the proposers do not feel to be in a position to give this information, they should take up contact with the scheduler (thum@iram.fr). The proposers should also specify on the cover sheet which receivers they plan to use.

In order to avoid useless duplication of observations and to protect already accepted proposals, we keep up a computerized list of targets. We ask you to fill out carefully the source list in equatorial J2000 coordinates. This list *must contain all the sources* (and only those sources) for which you request observing time. To allow electronic scanning of your

source parameters, your list must adhere to the format indicated on the proposal form (no hand writing, please). If your source list is longer (e.g. more than 15 sources) than what fits onto the cover page, please use the LaTeXmacro `\extendedsourcelist`.

A scientific project should not be artificially cut into several small projects, but should rather be submitted as one bigger project, even if this means 100–150 hours of observing time.

If time has already been given to a project but turned out to be insufficient, explain the reasons, e.g. indicate the amount of time lost due to bad weather or equipment failure; if the fraction of time lost is close to 100%, don't rewrite the proposal, except for an introductory paragraph. For continuation of proposals having led to publications, please give references to the latter.

Reminders

For any questions regarding the telescope and the control programs, we recommend to consult the NCS web pages (../IRAMES/ncs30m) and our page with the summary of telescope parameters.

The report entitled "Calibration of spectral line data at the IRAM 30m telescope" explains in detail the applied calibration procedure. Both documents can be retrieved from the URL ../IRAMES/otherDocuments/manuals/index.html. A catalog of well calibrated spectra for a range of sources and transitions (Mauersberger et al. [9]) is very useful for monitoring spectral line calibration. A copy of the 30m file with the calibrated spectra can be downloaded from the Spanish web site.

The astronomer on duty (whose schedule can be found at URL /IRAMES/mainWiki/-AstronomerOnDutySchedule) should be contacted well in advance for any special questions concerning the preparation of an observing run.

Frequency switching is available for both HERA and the single pixel SIS receivers. This observing mode is interesting for observations of narrow lines where flat baselines are not essential, although the spectral baselines with HERA are among the best known in frequency switching. Certain limitations exist with respect to maximum frequency throw ($\leq$ 45 km/s), backends, phase times etc.; for a detailed report see [4]. This report also explains how to identify mesospheric lines which may easily be confused in some cases with genuine astronomical lines from cold clouds.

Observing time estimates

This matter needs special attention as a serious time underestimate may be considered as a sure sign of sloppy proposal preparation. We strongly recommend to use the web–based Time Estimator at URL ../IRAMES/obstime/time_estimator.html , whenever applicable. Versions 2.6 and higher handle heterodyne (single pixel and HERA) as well as bolometer observations with updated instrumental parameters.

If very special observing modes are proposed which are not covered by the Time Estimator, proposers must give sufficient technical details so that their time estimate can be *reproduced*. In particular, the proposal must give values for $T_{\rm sys}$, the spectral resolution, the expected antenna temperature of the signal, the signal/noise ratio which is aimed for, all overheads and dead times, and the resulting observing time. The details of the procedures on which our time estimator is based are explained in a technical report published in the January 1995 issue[2] of the IRAM Newsletter [5].

Proposers should base their time request on normal summer conditions, corresponding to 7mm of precipitable water vapor. Conditions during afternoons can be degraded due to anomalous refraction. The observing efficiency is then reduced and the flux/temperature calibration is more uncertain than the typical 10 percent (possibly slightly more for bolometer observations). If exceptionally good transmission or stability of the atmosphere is requested which may be reachable only in winter conditions, the proposers must clearly say so in their time estimate paragraph. Such proposals will however be particularly scrutinized.

Pooled observing

As in previous semesters, we plan to pool the bolometer with other suitable proposals into a bolometer pool. HERA projects will be pooled with other less demanding project into a HERA pool. Both pools will be organized in several sessions, occupying a significant fraction of the totally available observing time. The proposals participating in the pools will be observed by IRAM staff, the PIs and Co-PIs of participating projects and other cooperating external astronomers. The pool observations will be organized by the pool coordinators, Stéphane Léon (bolometers) and Helmut Wiesemeyer (HERA). The participating proposals are

[2] electronically available at URL `../IRAMFR/ARN/-newsletter.html`

grouped according to their demand on weather quality, and they get observed following the priorities assigned by the program committee. The organization of the bolometer and the HERA observing pools are described at ../IRAMES/mainWiki/PoolObserving.

Bolometer and heterodyne proposals which are particularly weather tolerant qualify as backup for the pools. Participation in the pools is voluntary, and the respective box on the proposal form should be checked.

Questions concerning the pool organization can be directed to the scheduler (thum@iram.fr) or the Pool Coordinators, Stéphane Léon (leon@iram.es) and Helmut Wiesemeyer (wiesemeyer@iram.es).

Service observing

To facilitate the execution of short ($\leq$8 h) programmes, we propose "service observing" for some easy to observe programmes *with only one set of tunings*. Observations are made by the local staff using precisely laid–out instructions by the principal investigator. For this type of observation, we request an acknowledgement of the IRAM staff member's help in the forthcoming publication. If you are interested in this mode of observing, specify it as a "special requirement" in the proposal form. IRAM will then decide which proposals can actually be accepted for this mode.

Remote observing

This observing mode where the remote observer actually controls the telescope very much like on Pico Veleta, will be available from the downtown Granada office, and later during the summer also from Grenoble and possibly Bonn. The remote stations in Paris and Madrid will be available later.

Technical Information about the 30m Telescope

This section gives all the technical details of observations with the 30m telescope that the typical user will have to know. A concise summary of telescope characteristics is published on the IRAM web pages.

HERA

The **HE**terodyne **R**eceiver **A**rray is expected to be available for most of next summer. Whenever possible, HERA observations will be pooled. The 9 dual–polarization pixels are arranged in the form of a center–filled square and are separated by 24″. Each beam is split into two linear polarizations (after a successful upgrade in March 2005) which couple to separate SIS mixers. The 18 mixers feed 18 independent IF chains. Each set of 9 mixers is pumped by a separate local oscillator system. The same positions can thus be observed simultaneously at any two frequencies inside the HERA tuning range (210-276 GHz for the first polarization, and 210-242 for the second polarization).

A derotator optical assembly can be set to keep the 9 pixel pattern stationary in the equatorial or horizontal coordinates. Receiver characteristics are listed in Tab. 1, and an updated user manual (version 2.0) is available on our web page.

Frequency tuning of HERA, although fully under remote control and automatic, is substantially more complicated than for the observatory's other SIS receivers. HERA observers are therefore advised to send a list of their frequencies to Granada at least 2 weeks ahead of their run.

Recent observations have shown that the noise temperature of the pixels of the second polarization array may vary across the 1 GHz IF band. The highest noise occurs towards the band edges which are, unfortunately, picked up when HERA is connected with VESPA whose narrow observing band is located close to the lower edge of the 1 GHz band. Therefore, while not as important for wide band observations with centered IF band, the system noise in narrow mode is higher (factor $1.5 - 2$) as compared to the first polarization array. We do not recommend to use the second polarization for frequencies > 241 GHz.

HERA can be connected to three sets of backends:

- ▷ VESPA with the following combinations of nominal resolution (KHz) and maximum bandwidth (MHz): 20/40, 40/80, 80/160, 320/320, 1250/640. The maximum bandwidth can actually be split into two individual bands for each of the 18 detectors at most resolutions. These individual bands can be shifted separately up to ±200 MHz offsets from the sky frequency (see also the sections on backends below).
- ▷ a low spectral resolution (4 MHz channel spacing) filter spectrometer covering the full IF bandwidth of 1 GHz. Nine units (one per HERA pixel) are available. Note that only one polarization of the full array is thus connectable to these filter banks.
- ▷ WILMA with a 1 GHz wide band for each of the 18 detectors. The bands have 512 spectral channels spaced out by 2 MHz.

HERA will be operational in two basic spectroscopic observing modes: *(i)* raster maps[3] of areas typically not smaller than $1'$, in position, wobbler, or frequency switching modes, and *(ii)* on–the–fly maps of moderate size (typically $2' - 10'$). Extragalactic proposals should take into account the current limitations of OTF line maps, as described in the HERA User Manual, due to baseline instabilities induced by residual calibration errors. HERA proposers should use the web–based Time Estimator. For details about observing with HERA, consult the User manual. The HERA project scientist, Karl Schuster (schuster@iram.fr), or Albrecht Sievers (sievers@iram.es), the astronomer in charge of HERA, may also be contacted.

The single pixel heterodyne receivers

Four dual polarization SIS receivers are available at the telescope for the upcoming observing season. They are designated according to the dewar in which they are housed (A, B, C, or D), followed by the center frequency (in GHz) of their tuning range. Their main characteristics are summarised in Tab. 1. All receivers are linearly polarized with the E–vectors, before rotation in the Martin–Puplett interferometers, either horizontal or vertical in the Nasmyth cabin. Up to four of these eight receivers can be combined for simultaneous observations in the four ways depicted in Tab. 1. Note that they cannot be combined with HERA nor with the bolometers. Also listed are typical system temperatures which apply to average summer weather (7mm of water) at the center of the tuning range and at 45° elevation. All receivers are tuned by the operators from the control room. Experience shows that it normally takes not more than 15 min to tune four such receivers.

Extended tuning range: 72 – 80 GHz. Several molecules of high astrophysical importance have transitions in the frequency band 66 – 80 GHz, i.e. between the atmospheric O_2 absorption band and the low frequency edge of the nominal 3mm tuning range (see Tab.1). Tests have shown that both 3mm receivers, A 100 and B 100 have good performance (good upper sideband rejection and system temperature) in the range 80 – 77 GHz. The receivers become increasingly double sideband below 77 GHz, until their behavior becomes erratic around 72 GHz. Due to the rapid variation of the image gain, special care must be exercised with calibration. A new image gain calibration tool is provided and described in the test report available on the IRAM web site (at ../IRAMFR/PV/veleta.htm). The report includes a set of reference spectra.

Observations in the 72 – 80 GHz range do not require any special arrangements. But note that the A 230 (B 230) receiver is not available when the A 100 (B 100) receiver is used below 80 GHz.

General point about receiver operations. Tuning of the single pixel/dual polarization receivers is now considerably faster and more reproducible than before. Particular frequencies, like those in the range 72 – 80 GHz or those near a limit of the tuning range, may still be problematic. In these cases, we recommend to check with a Granada receiver engineer at least two weeks before the observations. HERA observers, however, are requested to send their frequencies as soon as their project gets scheduled.

Polarimeter XPOL. An upgrade of the IF polarimeter [16] is now available, where the cross correlation between the IF signals from a pair of orthogonally polarized receivers is made digitally in VESPA. The new observing procedure, designated XPOL, generates simultaneous spectra of all 4 Stokes parameters. The following combinations of spectral resolution (kHz) and bandwidth (MHz) are available: 40/120, 80/240, and 320/480.

Although successful XPOL observations were made at many frequencies, experience is still limited, particularly at 1.3mm wavelength and with respect to observations of extended sources. Considerable progress was made in reducing polarization sidelobes, notably for Stokes V. Interested users should contact C. Thum for details. Data reduction software using CLASS enhanced with a graphical user interface is available (H. Wiesemeyer). A short guide (at /IRAMFR/PV/veleta.htm) describes XPOL observations. Polarimetry proposals for observation of extended sources should demonstrate that their observations are feasible in the presence of the known sidelobes (see [16]).

MPIfR Bolometer arrays

The bolometer arrays, MAMBO–1 (37 pixels) and MAMBO–2 (117 pixels), are provided by the Max–Planck–Institut für Radioastronomie. They consist of concentric hexagonal rings of horns centered on the central horn. Spacing between horns is $\simeq 20''$. Each pixel has a HPBW of $11''$. We expect that

[3] As long as the NCS raster command is not operational, the raster pattern has to be traced out with the help of a SIC loop.

Table 1: Heterodyne receivers available for the next summer observing semester. Performance figures are based on recent measurements at the telescope. T^*_{sys} is the SSB system temperature in the T^*_A scale at the nominal center of the tuning range, assuming average summer conditions (pwv = 7mm) and 45° elevation. g_i is the rejection factor of the image side band. ν_{IF} and $\Delta\nu_{IF}$ are the IF center frequency and width.

receiver	polari–	combinations				tuning range	T_{Rx}(SSB)	g_i	ν_{IF}	$\Delta\nu_{IF}$	T^*_{sys}	remark
	zation	1	2	3	4	GHz	K	dB	GHz	GHz	K	
A 100	V	1		3		80 - 115.5	60 - 80	> 20	1.5	0.5	120	
B 100	H	1			4	81 - 115.5	60 - 80	> 20	1.5	0.5	120	1
C 150	V		2		4	129 - 183	70 - 125	15 - 25	4.0	1.0	200	
D 150	H		2	3		129 - 183	80 - 125	8 - 17	4.0	1.0	200	
A 230	V	1		3		197 - 266	85 - 150	12 - 17	4.0	1.0	450	2
B 230	H	1			4	197 - 266	95 - 160	12 - 17	4.0	1.0	450	2
C 270	V		2		4	241 - 281	125 - 250	10 - 20	4.0	1.0	1000	3
D 270	H		2	3		241 - 281	150 - 250	9 - 13	4.0	1.0	1000	3
HERA	H/V					210 - 276	110 - 380	~ 10	4.0	1.0	400	2, 4

1: tuning range extended to ≥ 72 GHz under special conditions (see text)
2: noise increasing with frequency
3: performance at $\nu < 275$ GHz; noisier above 275 GHz.
4: the V–array (2nd polarization) of HERA has slighly higher noise which may vary across the IF band; it should not be used for frequencies higher than 241 GHz.

MAMBO–2 will be normally used, but MAMBO–1 is kept as a backup.

The effective sensitivity of both bolometers for onoff observations is ~ 40 mJy s$^{\frac{1}{2}}$ and ~ 45 mJy s$^{\frac{1}{2}}$ for mapping. The *rms*, in mJy, of a MAMBO–2 map is typically

$$rms = 0.4 f \sqrt{v_{scan} \Delta s}$$

where v_{scan}, in arc sec/sec, is the velocity in the scanning direction and Δs, in arc sec, is the step size in the orthogonal direction. The factor f is 1 (2) for sources of size $< 30''$ ($> 60''$). It is assumed that the map is made large enough that all beams cover the source. The sensitivities apply to bolometric conditions (stable atmosphere), (τ(250GHz) ~ 0.3, elevation 45 deg, and application of skynoise filtering algorithms). In cases where skynoise filtering algorithms are not or not fully effective (e.g. extended source structure, atmosphere not sufficiently stable), the effective sensitivity is typically about a factor of 2 worse. For those projects, only atmospheric conditions with low skynoise (i.e. stable atmosphere, no clouds, little turbulence) are recommened unless the expected signal is about 1 Jy/beam or stronger.

The bolometer arrays are mostly used in two basic observing modes, ON/OFF and mapping. Previous experience with MAMBO–2 shows that the ON/OFF reaches typically an rms noise of ~ 2.3 mJy in 10 min of total observing time (about 200 sec of ON source, or about 400 sec on sky integration time) under stable conditions. Up to 30 percent lower noise may be obtained in perfect weather. In this observing mode, the noise integrates down with time t as $\sqrt{t}$ to rms noise levels below 0.4 mJy.

In the mapping mode, the telescope is scanning in the direction of the wobbler throw (default: azimuth) in such a way that all pixels see the source once. A typical single map[4] with MAMBO–2 covering a fully and homogeneously sampled area of $150'' \times 150''$ (scanning speed: $5''$per sec, raster step: $8''$) reaches an rms of 2.8 mJy/beam in 1.9 hours if skynoise filtering is effective. Much more time is needed (see Time Estimator) if sky noise filtering cannot be used. The area actually scanned ($8.0' \times 6.5'$) must be larger than the map size (add the wobbler throw and the array size ($4'$), the source extent, and some allowance for baseline determination) if the EHK–algorithm is used to restore properly extended emission. Shorter scans may lead to problems in restoring extended structure. Mosaicing is also possible to map larger areas. Under many circumstances, maps may be co–added to reach lower noise levels. If maps with an rms $\lesssim 1$ mJy are proposed, the proposers should contact R. Zylka (zylka@iram.fr).

[4] see also the Technical report by D. Teyssier and A. Sievers on a special fast mapping mode (IRAM Newsletter No. 41, p. 12, Aug. 1999).

The bolometers are used with the wobbling secondary mirror (wobbling at a rate of 2 Hz). The orientation of the beams on the sky changes with hour angle due to parallactic and Nasmyth rotations, as the array is fixed in Nasmyth coordinates and the wobbler direction is fixed with respect to azimuth during a scan. Bolometer proposals participating in the pool have their observations (maps and ONOFFs) pre-reduced by a data quality monitor which runs scripts in MOPSIC. This package, complete with all necessary scripts, is also installed for off-line data analysis in Granada and Grenoble. It is also available for distribution from the IRAM Data Base for Pooled Observations or directly from R. Zylka (zylka@iram.fr). The older software packages (NIC [7] and MOPSI [8]) are still available, but cannot process data obtained with the NCS.

Bolometer proposals will be pooled together like in previous semesters along with suitable heterodyne proposals as long as the respective PIs agree. The web–based time estimator handles well the usual bolometer observing modes, and its use is again strongly recommended. The time estimator uses rather precise estimates of the various overheads which will be applied to all bolometer proposals. If exceptionally low noise levels are requested which may be reachable only in a perfectly stable (quasi winter) atmosphere, the proposers must clearly say so in their time estimate paragraph. Such proposals will however be particularly scrutinized. On the other extreme, if only strong sources are observed and moderate weather conditions are sufficient, the proposal may be used as a backup in the observing pool. The proposal should point out this circumstance, as it affects positively the chance that the proposal is accepted and observed.

Table 2: Main observational parameters of 30m telescope.

frequency [GHz]	θ_b ["] (1)	η_F (2)	η_{mb} (3)	S_ν/T_A^* [Jy/K]
86	29	0.95	0.78	6.0
110	22	0.95	0.75	6.3
145	17	0.93	0.69	6.7
170	14.5	0.93	0.65	7.1
210	12	0.91	0.57	7.9
235	10.5	0.91	0.51	8.7
260	9.5	0.88	0.46	9.5
279	9	0.88	0.42	10.4

(1) beam width (FWHP). A fit to all data gives: θ_b ["] = 2460 / frequency [GHz]
(2) forward efficiency (coupling efficiency to sky)
(3) main beam efficiency. Based on a fit of measured data to the Ruze formula:
$\eta_{\mathrm{mb}} = 1.2\epsilon \exp(-(4\pi R\sigma/\lambda)^2)$
with $\epsilon = 0.69$ and $R\sigma = 0.07$

The Telescope

Beam and Efficiencies

Table 2 lists the size of the telescope beam for the range of frequencies of interest. Forward and main beam efficiencies are also shown (see also the note by U. Lisenfeld and A. Sievers, IRAM Newsletter No. 47, Feb. 2001). The variation of the coupling efficiency to sources of different sizes can be estimated from plots in Greve et al. [12].

At 1.3 mm (and a fortiori at shorter wavelengths) a large fraction of the power pattern is distributed in an error beam which can be approximated by two Gaussians of FWHP $\simeq 170''$ and $800''$ (see [12] for details). Astronomers should take into account this error beam when converting antenna temperatures into brightness temperatures. A variable and sometimes large contribution to the error beam was known to come from telescope astigmatism [3]. Extensive work during the last years had shown that the astigmatism resulted from temperature differences between the telescope backup structure and the yoke. The recent installation of heaters in the yoke by J. Peñalver has nearly completely removed the astigmatism [15].

Pointing and Focusing

With the systematic use of inclinometers the telescope pointing became much more stable. Pointing sessions are now scheduled at larger intervals. The fitted pointing parameters typically yield an absolute rms pointing accuracy of better than $3''$ [10]. An effort is made that receivers are closely aligned. Checking the pointing, focus, and receiver alignment is the responsibility of the observers (use a planet for alignment checks). Systematic (up to 0.4 mm) differences between the foci of various receivers can occasionally occur. In such a case the foci should be carefully monitored and a compromise value be chosen. Not doing so may result in broadened and distorted beams ([1]).

Wobbling Secondary

- Beam–throw is $\leq 240''$ depending on wobbling frequency. At 2 Hz, the maximum throw is $90''$
- Standard phase duration: 2 sec for spectral line observations, 0.25 sec for continuum observations.

Unnecessarily large wobbler throws should be avoided, since they introduce a loss of gain, particularly at the higher frequencies, and imply a loss of observing efficiency (more dead time).

Backends

The following four spectral line backends are available which can be individually connected to any single pixel receiver and, if indicated, also to HERA.

The 1 MHz filterbank consists of 4 units. Each unit has 256 channels with 1 MHz spacing and can be connected to different or the same receivers giving bandwidths between 256 MHz and 1024 MHz. The maximum bandwidth is available for only one receiver, naturally one having a 1 GHz wide IF bandwidth. Connection of the filterbank in the 1 GHz mode presently excludes the use of any other backend with the same receiver.

Other configurations of the 1 MHz filterbank include a setup in 2 units of 512 MHz connected to two different receivers, or 4 units of 256 MHz width connected to up to four (not necessarily) different receivers. Each unit can be shifted in steps of 32 MHz relative to the center frequency of the connected receiver.

The 100 kHz filterbank consists of 256 channels of 100 kHz spacing. It can be split into two halves, each movable inside the 500 MHz IF bandwidth, and connectable to two different single pixel receivers (must be set up in narrow band mode).

VESPA, the versatile spectrometric and polarimetric array, can be connected either to HERA or to a subset of 4 single pixel receivers, or to a pair of single pixel receivers for polarimetry. The many VESPA configurations and user modes are summarized in a Newsletter contribution [14] and in a user guide, but are best visualised on a demonstration program which can be downloaded from our web page at URL /IRAMFR/PV/veleta.htm. Connected to a set of 4 single pixel receivers, VESPA typically provides up to 12 000 spectral channels (on average 3 000 per receiver). Up to 18 000 channels are possible in special configurations. Nominal spectral resolutions range from 3.3 kHz to 1.25 MHz. Nominal bandwidths are in the range 10 — 512 MHz. When VESPA is connected to HERA, up to 18 000 spectral channels can be used with the following typical combinations of nominal resolution (kHz) and maximum bandwidth (MHz): 20/40, 40/80, 80/160, 320/320, 1250/640.

The 4 MHz filterbank consists of nine units. Each unit has 256 channels (spacing of 4 MHz, spectral resolution at 3 dB is 6.2 MHz) and thus covers a total bandwidth of 1 GHz. The 9 units are designed for connection to HERA, but a subset of 4 units can also be connected to the backend distribution box which feeds the single pixel spectral line receivers. All these receivers have a 1 GHz RF bandwidth except for A100 and B100 (500 MHz only). At the present time, a 4 MHz filterbank cannot be used simultaneously with the autocorrelator or the 100 kHz filterbank on the same receiver.

The **wideband autocorrelator WILMA** consists of 18 units. They can be connected to the 18 detectors of HERA. Each unit provides 512 spectral channels, spaced out by 2 MHz and thus covering a total bandwidth of 1 GHz. Each band is sliced into two 500 MHz subbands which are digitized with 2 bit/1 GHz samplers. An informative technical overview of the architecture is available at URL ../IRAMFR/-TA/backend/veleta/wilma/index.htm. Note that WILMA cannot presently be connected to any of the single pixel receivers.

References

[1] Appendix I: Error beam and side lobes of the 30 m telescope at 1.3 mm, 2 mm and 3 mm wavelength, in "Molecular Spiral Structure in Messier 51",
S. Garcia-Burillo, M. Guélin, J. Cernicharo 1993, Astron. Astrophys. **274**, 144-146.

[2] A Small Users' Guide to NOD2 at the 30m telescope A. Sievers (Feb. 1993)

[3] Astigmatism in reflector antennas: measurement and correction
A. Greve, B. Lefloch, D. Morris, H. Hein, S. Navarro 1994, IEEE Trans. Ant. Propag. AP–42, 1345

[4] Frequency switching at the 30m telescope
C. Thum, A. Sievers, S. Navarro, W. Brunswig, J. Peñalver 1995, IRAM Tech. Report 228/95. (/IRAMES/otherDocuments/manuals/-Report/fsw_doc.ps)

[5] Cookbook formulae for estimating observing times at the 30m telescope
M. Guélin, C. Kramer, and W. Wild
(IRAM Newsletter January 1995)

[6] The 30m Manual: A Handbook for the 30m Telescope (version 2), W. Wild 1995
IRAM Tech. Report 377/95, also available on the web at ../IRAMES/otherDocuments/-manuals/manual_v20.ps

[7] NIC: Bolometer User's Guide
D. Broguière, R. Neri, A. Sievers, and H. Wiesemeyer
2000, IRAM Technical Report (../IRAMFR/-GILDAS/doc/html/nic-html/nic.html);
see also the GILDAS home page at /IRAMFR/GILDAS/ with further relevant technical reports.

[8] Pocket Cookbook for MOPSI software
R. Zylka 1996, available at ../IRAMES/otherDocuments/manuals/-Datared/pockcoo.ps.

[9] Line Calibrators at $\lambda = 1.3$, 2, and 3mm.
R. Mauersberger, M. Guélin, J. Martín–Pintado, C. Thum, J. Cernicharo, H. Hein, and S.Navarro 1989, A&A Suppl. 79, 217

[10] The Pointing of the IRAM 30m Telescope
A. Greve, J.–F. Panis, and C. Thum 1996, A&A Suppl. 115, 379

[11] The gain–elevation correction of the IRAM 30m Telescope
A. Greve, R. Neri, and A. Sievers 1998, A&A Suppl. 132, 413

[12] The beam pattern of the IRAM 30m Telescope
A. Greve, C. Kramer, and W. Wild 1998, A&A Suppl. 133, 271

[13] A Time Estimator for Observations at the IRAM 30m Telescope, D. Teyssier 1999, IRAM/Granada Technical Note (/IRAMES/-obstime/time_estimator.html)

[14] VESPA is operational
G. Paubert & C. Thum 2002,
IRAM Newsletter No. 54, 6
(/IRAMFR/PV/veleta.htm and /IRAMES-/otherDocuments/manuals/vespa_ug.ps)

[15] First results from the IRAM 30m telescope improved thermal control system
J. Peñalver, A. Greve, and M. Bremer 2002, IRAM Newsletter No. 54, 8

[16] A Versatile IF Polarimeter at the IRAM 30m Telescope
C. Thum, H. Wiesemeyer, D. Morris, S. Navarro, and M. Torres
in "Polarimetry in Astronomy", Ed. S.Fineschi, Proc.of SPIE Vol.4843, 272–283 (2003)

These reports are available upon request (see also previous Newsletters). Please write to Mrs. C. Berjaud, IRAM Grenoble (e–mail: `berjaud@iram.fr`).

Clemens Thum & Rainer Mauersberger

News from the Plateau de Bure Interferometer

Following the successful installation and commissioning of the Next Generation Receivers (NGRs) for the 3 mm and 1.3 mm atmospheric windows last fall, regular observing was resumed on January 18th, 2007 when the array was in its 6D configuration. We switched to the A configuration (that provides baselines up to 760m) was achieved on January 28 and the baselines were determined with high precision (better than 14 deg phase rms at 86 GHz on the longest baselines). It is planned to move to the B configuration around end of February and to the C configuration by end of March. The switch back to the most compact configuration D is foreseen before end of April. According to these plans, it will not be possible to complete projects requesting deep integrations using the compact configurations before the end of the current observing period.

The observing conditions in January were quite mediocre due to the unusually warm winter in Europe, but they improved considerably by the end of the month. Only commissioning projects were observed with the NGR system in D configuration but as of February 13 already 17 tracks have been scheduled in A configuration for regular user projects.

As far as A-rated projects are concerned, we look forward to bring many of these to completion before the end of the current winter semester. B-rated projects are likely to be observed only if they fall in a favorable LST range. We remind users of the Plateau de Bure interferometer that B-rated proposals which are not started before the end of the winter period have to be resubmitted.

Global VLBI observations, which include the array in the 3mm phased-array mode, are planned from May 10 to 15, 2007.

Investigators, who wish to check the status of their project, may consult the interferometer schedule on the Web at ../PDBI/ongoing.html. The page is updated daily.

Jan Martin WINTERS

Call for Observing Proposals on the Plateau de Bure Interferometer

Conditions for the next summer period

As every year, we plan to carry out extensive technical work during the summer semester, including the regular maintenance of the antennas. During this period, regular scientific observations will therefore mostly be carried out with the five element array. In addition to the antenna maintenance, an upgrade of the computer system on Bure will be carried out. All HPUX and OS9 systems will be replaced by LINUX PCs along with major modifications of the corresponding antenna control and data acquisition software in the real-time system. Further work will be done on the reduction of the sun avoidance circle. Finally, new receivers operating in the 2 mm band will be installed on all six antennas. This new set of receivers, which will open a new frequency band at the Plateau de Bure interferometer, will be become available for the community at the end of the summer semester, after thorough testing and commissioning.

We plan to start the maintenance at the latest by the end of May and to schedule the 5D configuration between June and September. Scheduling of the 6D and 6C configurations will be tailored to progress being made in the commissioning of the 2 mm NGR system.

We strongly encourage observers to submit proposals that can be executed during summer operating conditions. To keep the procedure as simple as possible, we ask to focus on:

- observations requesting the use of the 3mm receivers
- circumpolar sources or sources transiting at night between June and September,
- observations that qualify for the 5D, 6D, and 6C configurations

Proposal category

Proposals should be submitted for one of the four categories:

1.3MM: Proposals that ask for 1.3mm data. 3mm receivers can be used for pointing and calibration purposes, but cannot provide any imaging.

3MM: Proposals that ask for 3mm data.

TIME FILLER: Proposals that have to be considered as background projects to fill in periods where the atmospheric conditions do not allow mapping, or eventually, to fill in gaps in the scheduling, or even periods when only a subset of the standard 5-antenna configurations will be available. These proposals will be carried out on a "best effort" basis only.

SPECIAL: Exploratory proposals: proposals whose scientific interest justifies the attempt to use the PdB array beyond its guaranteed capabilities. This category includes for example non-standard frequencies for which the tuning cannot be guaranteed, non-standard configurations and more generally all non-standard observations. These proposals will be carried out on a "best effort" basis only.

The proposal category will have to be specified on the proposal cover sheet and should be carefully considered by proposers.

Configurations

Configurations planned for the summer period are:

Name	Stations
5Dq	W08 E03 N07 N11 W05
6Dq	W08 E03 N07 N11 N02 W05
6Cq	W12 E10 N17 N11 E04 W09

Part of the projects will be scheduled at the end of the summer period when the six-element array is expected to be back to operation. Projects that should be observed with a subset of the five-element array, will be adjusted in uv-coverage and observing time.

The following configuration sets are available:

Set	Main purpose
D	Detection + "low" resolution mapping at 1.3mm
CD	3.5″ resolution mapping at 3mm

Finally, enter ANY in the proposal form if your project doesn't need any particular configuration.

Receivers

Since December 2006 all antennas are equipped with a new generation of dual polarization receivers for the 3 mm and 1.3 mm atmospheric windows. The frequency range is 81 GHz to 116 GHz for the 3 mm band, and 201 to 256 GHz for the 1.3 mm band.

Each band of the new receivers is dual-polarization (two RF and IF channels) with the two RF channels of one band observing at the same frequency (common LO). The different bands are not co-aligned in the focal plane (and therefore on the sky). The mixers are single-sideband, backshort-tuned; they can be tuned USB or LSB, both choices being available in the central part of the RF band. The typical image rejection is 10 dB. Each IF channel is 4 GHz wide (4-8 GHz). Only one frequency band can be connected to the IF transmission lines at any time. Because of this reason and due to the pointing offsets between different frequency bands, only one band can be observed at any time. The other band is in stand-by (power on and local oscillator phase-locked) and is available, e.g., for pointing. Time-shared observations between two frequency bands can not be offered for the summer (this mode is currently being tested).

The two IF-channels (one per polarization), each 4 GHz wide (total 8 GHz) are transmitted by optical fibers to the central building. At present, the 4 GHz bandwidth can be processed only partially by the existing correlator, through a dedicated IF processor that converts selected 1 GHz wide slices of the 4-8 GHz first IFs down to 0.1-1.1 GHz, the input range of the existing correlator. Further details are given in the section describing the correlator setup and the IF processor.

PdBI Receiver Specifications		
	Band 1	Band 3
RF coverage	81–116	201–256
T_{rec}	40–55	40–60 (LSB)
T_{rec}		50–70 (USB)
G_{im}	−10 dB	−12 − 8 dB
RF range in LSB	81–104	201–244
RF range in USB	104–116	244–256

Signal to Noise

The rms noise can be computed from

$$\sigma = \frac{J_{\rm pK} T_{\rm sys}}{\eta \sqrt{N_{\rm a}(N_{\rm a}-1) N_{\rm c} T_{\rm ON} B}} \frac{1}{\sqrt{N_{\rm pol}}} \qquad (1)$$

where

- $J_{\rm pK}$ is the conversion factor from Kelvin to Jansky (22 Jy/K at 3 mm, 35 Jy/K at 1.3 mm)
- $T_{\rm sys}$ is the system temperature ($T_{\rm sys}$ = 100 K below 110 GHz, 180 K at 115 GHz, 250 K at 230 GHz for sources at $\delta \geq 20°$ and for typical summer conditions.)

- η is an efficiency factor due to atmospheric phase noise (0.9 at 3 mm, 0.8 at 1.3 mm).
- N_a is the number of antennas (5), and N_c is the number of configurations: 1 for D, 2 for CD, and so on.
- T_{ON} is the on-source integration time per configuration in seconds (2 to 8 hours, depending on source declination). Because of various calibration observations the total observing time is typically 1.4 T_{ON}.
- B is the spectral bandwidth in Hz (up to 2 GHz for continuum, 40 kHz to 2.5 MHz for spectral line, according to the spectral correlator setup)
- N_{pol} is the number of polarizations: 1 for single polarization and 2 for dual polarization (see section *Correlator* for details).

Investigators have to specify the one sigma noise level which is necessary to achieve each individual goal of a proposal, and particularly for projects aiming at deep integrations.

Coordinates and Velocities

The interferometer operates in the J2000.0 system. For best position accuracy, source coordinates must be in the J2000.0 system; position offsets up to 0.3″ may occur otherwise.

Please do not forget to specify LSR velocities for the sources. For pure continuum projects, the "special" velocity `NULL` (no Doppler tracking) can be used.

Coordinates and velocities in the proposal MUST BE CORRECT: A coordinate error is a potential cause for proposal rejection.

Correlator

IF processor

At any given time, only one frequency band is used, but with the two polarizations available. Each polarization delivers a 4 GHz bandwidth (from IF=4 to 8 GHz). The two 4-GHz bandwidths coincide in the sky frequency scale. The current correlator accepts as input two signals of 1 GHz bandwidth, that must be selected within the 4 GHz delivered by the receiver. In practice, the new IF processor splits the two input 4–8 GHz bands in four 1 GHz "quarters", labeled *Q1...Q4*. Two of these quarters must be selected as correlator inputs. The system allows the following choices:

- first correlator entry can only be Q1 HOR, or Q2 HOR, or Q3 VER, or Q4 VER
- second correlator entry can only be Q1 VER, or Q2 VER, or Q3 HOR, or Q4 HOR

where HOR and VER refers to the two polarizations:

Quarter	Q1	Q2	Q3	Q4
IF1 [GHz]	4.2 – 5.2	5 – 6	6 – 7	6.8 – 7.8
input 1	H	H	V	V
input 2	V	V	H	H

How to observe two polarizations? To observe simultaneously two polarizations at the same sky frequency, one must select the same quarter (Q1 or Q2 or Q3 or Q4) for the two correlator entries. This will necessarily result in each entry seeing a different polarization. The system thus give access to 1 GHz × 2 polarizations.

How to use the full 2 GHz bandwidth? If two different quarters are selected (any combination is possible), a bandwidth of 2 GHz can be analyzed by the correlator. But only one polarization per quarter is available in that case; this may or may not be the same polarization for the two chunks of 1 GHz.

Is there any overlap between the four quarters? In fact, the four available quarters are 1 GHz wide each, but with a small overlap between some of them: Q1 is 4.2 to 5.2 GHz, Q2 is 5 to 6 GHz, Q3 is 6 to 7 GHz, and Q4 is 6.8 to 7.8 GHz. This results from the combination of filters and LOs used in the IF processor.

Is the 2 GHz bandwidth necessarily continuous? No: any combination of two quarters can be selected. Adjacent quarters will result in a continuous 2 GHz band. Non-adjacent quarters will result in two independent 1 GHz bands. Note that in any case, the two correlator inputs are analyzed independently.

Where is the selected sky frequency in the IF band? It would be natural to tune the receivers so that the selected sky frequency corresponds to the middle of the IF bandwidth, i.e. 6.0 GHz. However, this corresponds to the limit between Q2 and Q3. It is therefore highly recommended to center a line at the center of a quarter (see Section "ASTRO" below). At 3 mm, the receivers offer best performance in terms of receiver noise and sideband rejection in Q2 (i.e. the line should be centered at an IF1 frequency of 5500 MHz) whereas at 1 mm best performance is obtained in Q3 (i.e. the line should be centered at 6500 MHz).

Spectral units of the correlator

The correlator has 8 independent units, which can be placed anywhere in the 100–1100 MHz band (1 GHz bandwidth). 7 different modes of configuration are available, characterized in the following by couples of total bandwidth/number of channels. In the 3 DSB modes (320MHz/128, 160MHz/256, 80MHz/512 – see Table) the two central channels may be perturbed by the Gibbs phenomenon if the observed source has a strong continuum. When using these modes, it is recommended to avoid centering the most important part of the lines in the middle of the band of the correlator unit. In the remaining SSB modes (160MHz/128, 80MHz/256, 40MHz/512, 20MHz/512) the two central channels are not affected by the Gibbs phenomenon and, therefore, these modes may be preferable for some spectroscopic studies.

Spacing (MHz)	Channels	Bandwidth (MHz)	Mode
0.039	1×512	20	SSB
0.078	1×512	40	SSB
0.156	2×256	80	DSB
0.312	1×256	80	SSB
0.625	2×128	160	DSB
1.250	1×128	160	SSB
2.500	2×64	320	DSB

Note that 5% of the passband is lost at the end of each subband. The 8 units can be independently connected to the first or the second correlator entry, as selected by the IF processor (see above). Please note that the center frequency is expressed – as in the old system – in the frequency range seen by the correlator, i.e. 100 to 1100 MHz. The correspondence to the sky frequency depends on the parts of the 4 GHz bandwidth which have been selected as correlator inputs.

ASTRO

The software `ASTRO` has been updated to reflect these new receiver/correlator setup possibilities. Astronomers are urged to download the most recent version (**February 2007 or later**) of GILDAS at `../IRAMFR/GILDAS/` to prepare their proposals.

The old `LINE` command has been replaced by several new commands (see internal help):

- `NGR_LINE`: receiver tuning
- `NARROW`: selection of the narrow-band correlator inputs
- `SPECTRAL`: spectral correlator unit tuning
- `PLOT`: control of the plot parameters.

A typical session would be:

```
! choice of receiver tuning
ngr_line xyz 230 lsb

! choice of the correlator windows
narrow Q1 Q3

! correlator unit #1, on entry 1
spectral 1  20 520 /narrow 1

! correlator unit #2, on entry 1
spectral 2 320 260 /narrow 1

! correlator unit #3, on entry 2
spectral 3  40 666 /narrow 2
...
```

Sun Avoidance

For safety reasons, the sun avoidance circle has been extended to 45 degrees. Please take this into account for your target sources AND for the calibrators.

Mosaics

The PdBI has mosaicing capabilities, but the pointing accuracy may be a limiting factor at the highest frequencies. Please contact the Science Operations Group (sog@iram.fr) in case of doubts.

Data reduction

Proposers should be aware of constraints for data reduction:

- In view of the new receiver system, **data have to be reduced in Grenoble**. Proposers will not come for the observations, but will have to come for the reduction. For the time being, remote data reduction will not be offered for projects observed with the NGR system.
- We keep the data reduction schedule very flexible, but wish to avoid the presence of more than 2 groups at the same time in Grenoble. Data reduction will be carried out on dedicated computers at IRAM. Please contact us in advance.
- In certain cases, proposers may have a look at the uv-tables as the observations progress.

If necessary, and upon request, more information can be provided. Please contact your local contact or the Science Operations Group (sog@iram.fr) if you are interested in this.

- CLIC evolves to cope with upgrades of the PdBI array. The newer versions are downward compatible with the previous releases. Observers who wish to finish NGR data reduction at their home institute should obtain the most recent version of CLIC. Because differences between CLIC versions may potentially result in imaging errors if new data are reduced with an old package, we advise observers having a copy of CLIC to take special care in maintaining it up-to-date. The upgrade of CLIC to handle the NGR data implied many modifications for which backward compatibility with old PdBI receiver data has not yet been fully checked. To calibrate data obtained with the "old" receiver system, we thus urge you to use the January 2007 version of CLIC.

Local Contact

A local contact will be assigned to every A or B rated proposal which does not involve an in-house collaborator. He/she will assist you in the preparation of the observing procedures and provide help to reduce the data. Assistance is also provided before a deadline to help newcomers in the preparation of a proposal. Depending upon the program complexity, IRAM may require an in-house collaborator instead of the normal local contact.

Technical pre-screening

All proposals will be reviewed for technical feasibility in parallel to being sent to the members of the program committee. Please help in this task by submitting technically precise proposals. Note that your proposal must be complete and exact: the source position and velocity, as well as the requested frequency setup must be correctly given.

Non-standard observations

If you plan to execute a non-standard program, please contact the Interferometer Science Operations Group (sog@iram.fr) to discuss the feasibility.

Documentation

The documentation for the IRAM Plateau de Bure Interferometer includes documents of general interest to potential users, and more specialized documents intended for observers on the site (IRAM on-duty astronomers, operators, or observers with non-standard programs). All documents can be retrieved on the Internet at `../IRAMFR/PDB/docu.html`
Note however, that the documentation on the web has not yet been updated with respect to the new generation receivers. All information currently available on the new generation receiver system is given in this call for proposals.

Finally, we would like to stress again the importance of the quality of the observing proposal. The IRAM interferometer is a powerful, but complex instrument, and proposal preparation requires special care. Information is available in this call and at `../IRAMFR/PDB/docu.html`. The IRAM staff can help in case of doubts if contacted well before the deadline. Note that the proposal should not only justify the scientific interest, but also the need for the Plateau de Bure Interferometer.

Jan Martin WINTERS